### VITRIFIED TILES



























Thinkness: **9mm** 

Size: 600x1200mm







Randonnio














Thinkness: **9mm** Size: 600x1200mm

























# MATT600xFINISH1200





#### **GLIMPSE SATIN WHITE**



### Application







Terrace



## **GLOSSY** 600x FINISH 1200





#### **GLIMPSE POLISH WHITE**



### Application



## MATT600xFINISH1200





**GLIMPSE BLACK** 



#### Application







## MATT600xFINISH1200





SLATE GREY



#### Application





Furniture Tops









#### **MOSAIC WHITE**



### Application









## MATT 600x FINISH 1200





#### SLATE CREMA



#### Application





Furniture Focode Tops





## MATT600xFINISH1200





#### **FLOAT CREMA**



### Application





Terrace



### **MATT** | 600x FINISH | 1200





#### **FLOAT GREY**



#### Application







Terrace



## **MATT** | 600x FINISH | 1200





**MOSAIC NERO** 



### Application









## **MATT** | 600x FINISH | 1200





**SLATE NERO** 



### Application





Facade

Terrace

Ť



### SPECIFICATION OF FULL BODY VITRIFIED TILES

Sr.No	CHARACTERISTICS	STANDARD AS PER IS 15622:2006 GROUP BIA	MEAN VALUE
Regulatory	Properties		
1	Deviation in Length & Width	±0.5%	±0.1%
2	Deviation in Thickness	±5.0%	±3.0%
3	Straightness of Sides	±0.5%	±0.1%
4	Rectrangularity	±0.5%	±0.1%
5	Surface Flatness	±0.5%	±0.2%
6	Glossiness	As per mfg.	Matt surface
Structural	Properties		
7	Water Absorption	<0.5%	≤0.10%
8	Apparent Density	>2.0 g/cc	>2.10 g/cc
Massive Me	echanical Properties		
9	Modulus Rupture	Min. 35 N/mm <sup>2</sup>	Min. 40 N/mm <sup>2</sup>
10	Impact Resistance	As per mfg.	Min. 0.55
Surface Me	chanical Properties		
11	Surface abrasion resistance	As per mfg.	Min. Class 5
12	MOH's Hardness	As per mfg.	Min. 5
Thermo Hy	drometric Properties		
13	Frost Resistance	No Damage	No Damage
14	Thermal Shock Resistance	No Damage	No Damage
15	Moisture Expansion	Nil	Nil
16	Crazing Resistance	No Damage	Min. 10 Cycle
Chemical P	roperties		
17	Chemical Resistance	No Damage	No Damage
18	Stain Resistance	Resistance	Resistance
Safety Prop	perties		
19	Anti Skid (COF)	As per mfg.	Matt <0.75
20	Fire Resistance	As per mfg.	Fire Proof

PACKING DETAILS					
SIZE	THICKNESS	TILES PER BOX	COVERAGE AREA (Approx)		
600x1200mm	9 mm (Approx)	2 pcs	1.44 sq.mtr.		



www.volarktiles.com